



SEE STANDARD PLAN S-3 FOR ADDITIONAL TYPICAL SIDEWALK DETAILS

DETECTABLE WARNING PATTERN

(URBAN) ARTERIAL ROADWAY

CEMENT CONCRETE SIDEWALK RAMP (TYP.)

CEMENT CONCRETE PEDESTRIAN CURB

RADIUS (VARIES)
(SEE PLANS)

10'
TRANSITION

0.5'

1.5'

5'

(URBAN) ACCESS ROADWAY

PLAN VIEW
NTS

RADIUS AT FACE OF CURB	F
20'	7.69'
25'	6.94'
30'	6.52'
35'	6.33'
40'	6.06'
45'	5.92'
50'	5.81'
DIMENSIONS AT FACE OF CURB	

NOTES:

- 1) CURB RAMP DIMENSIONS ARE AT BACK OF SIDEWALK.
- 2) DETECTABLE WARNING PATTERN AREA SHALL MEET THE REQUIREMENTS SET FORTH ON WSDOT STANDARD PLAN F-45.10-00.
- 3) SIDEWALK SEE S-3.

SIDEWALK HANDICAP CURB RAMP LOCATION



APPROVED BY: *[Signature]* DATE: 5/14/15
County Engineer:

REVISION:	DESCRIPTION:	DATE:

STANDARD PLAN
S-6
SHEET 1 OF 1